


XGQT2

Flexible Coupling



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimension			Bolt/Nut
			A	B	C	
			mm/in	mm/in	mm/in	
25	33.7	300	56	96	45	M10*45
1	1.327	2.07	2.205	3.780	1.772	M10*45
32	42.4	300	66	106	45	M10*45
1 1/4	1.669	2.07	2.598	4.173	1.772	M10*45
40	48.3	300	72	114	45	M10*45
1 1/2	1.9	2.07	2.835	4.488	1.772	M10*45
50	60.3	300	81	126	47	M10*55
2	2.375	2.07	3.189	4.961	1.850	M10*55
65	73	300	95	139	47	M10*55
2 1/2	2.875	2.07	3.740	5.472	1.850	M10*55
65	76.1	300	99	143	47	M10*55
3OD	3	2.07	3.898	5.630	1.850	M10*55
80	88.9	300	112	157	48	M10*55
3	3.5	2.07	4.409	6.181	1.890	M10*55
100	114.3	300	138	193	50	M12*65
4	4.5	2.07	5.433	7.598	1.969	M12*65
125	139.7	300	166	221	50	M12*70
5 1/2 OD	5.5	2.07	6.535	8.701	1.969	M12*70
150	165.1	300	193	250	51	M12*70
6 1/2 OD	6.5	2.07	7.598	9.843	2.008	M12*70
150	168.3	300	196	256	51	M12*70
6	6.625	2.07	7.717	10.079	2.008	M12*70
200	219.1	300	254	322	63	M16*85
8	8.625	2.07	10.000	12.677	2.480	M16*85
250	273	300	313	392	64	M20*100
10	10.75	2.07	12.323	15.433	2.520	M20*100
300	323.9	300	366	445	66	M20*110
12	12.75	2.07	14.409	17.520	2.598	M20*110